

SP SPRINT

PNEUMATIC PRECISION PLANTER (corn-sunflower-soya)



Suffolk coulter

STANDARD EQUIPMENT

Planting unit with shoe opener and clod pusher
 Rear press wheels (specify type)
 1 standard seed plate each row (specify seed type)
 Three point hitch with floating 1st and 2nd points, cat. II
 Pair of transmission gears
 1" 3/8 Z6-Z6 PTO shaft (length 700)
 Automatic row marker (track on wheel - fixed for 2 rows)
 8 rows 75 cm with hydraulic row marker
 Centralized SPEEDY SET adjustment for MINIMAX fertilizer dosers

Vacuum gauge
 Lighting kit (disassembled)
 Warning boards (disassembled)

Drive wheels:
 STANDARD n°2 rear 5.00-15
 6 rows 75: n°2 rear 6.50-15
 8 rows 75: n°4 rear 6.50-15

SP - ST planting unit

PNEUMATIC PRECISION PLANTER STANDARD PLANTING UNIT



1	Double parallelogram
2	Pressure and/or relief spring
3	Rapid release of planting unit
4	Fast opening for easy seed plate replacement, low-friction gasket
5	Plastic hopper - 34 l.
6	Seeding depth adjustment
7	Seed selector

8	Rear compression wheel (farmflex, rubber Ø 290, "V" shaped 2" rubber type, "V" shaped 1" rubber type)
9	Furrow covering unit to make sure the seeding furrow is filled
10	Aluminium distributor
11	Coulter featuring special profile with interchangeable tip
12	Adjustable clod breaker
13	Cardan drive transmission with quick release, acoustic safety device, low maintenance
14	Sinterized self-lubricating bushings



MEDIUM DEPTH PLANTING

Depending on the way the rear wheel is set, the maximum depth of the seeding furrow can vary from 7 to 10 cm



Seed boot coulter for thoroughly prepared soil.



Double-disc furrow coulter. For rough soil with residuals.

SUPERFICIAL PLANTING

Depending on the way the rear wheel is set, the maximum depth of the seeding furrow can vary from 3.5 to 5 cm



Shallow seeding furrow coulter features double rubber wheels and two rubber wheels and one smaller seed press wheel mounted behind the spike



Seed expulsion unit for sugarbeet version

PRESS WHEEL



Farmflex rubber wheel
Ø 370 mm (with front seed press) For finely prepared and/or sandy soil



2° V shaped rubber press wheel. For medium-textured soils also wet, all purpose use



1° V shaped rubber press wheel. For hard soil, also wet.

Version	Model	Row spacing cm	Fertilizer n°1	Frame cm	Weight kg	Code	Price €
BASIC	SP - 2 R	75		190	330	G96102213	7 205
	SP - 4 R [15]	75		250	550	G96104213	10 795
	SP - 5 R	75		320	615	G96105213	12 680
	SP - 6 R [15]	45		250	662	G96106113	14 025
	SP - 6 R	75		420	692	G96106253	14 765
	SP - 8 R	45		420	890	G96108113	18 245
	SP - 8 R	75		580	930	G96108263	20 490
MICROGRANULATOR	SP - 2 R	75		190	358	G96102813	8 360
	SP - 4 R [15]	75		250	585	G96104813	12 465
	SP - 5 R	75		320	685	G96105813	14 775
	SP - 6 R [15]	45		250	705	G96106713	16 210
	SP - 6 R	75		420	735	G96106853	16 950
	SP - 8 R	45		420	980	G96108713	20 945
	SP - 8 R	75		580	1005	G96108863	23 680
FERTILIZER	SP - 2 R [9]	75	2x90	190	390	G96102413	9 140
	SP - 4 R [15]	75	2x160	250	690	G96104413	13 470
	SP - 5 R	75	2x160	320	770	G96105413	15 575
	SP - 6 R [15]	45	2x160	250	845	G96106313	17 140
	SP - 6 R [9]	75	2x280	420	875	G96106453	18 540
	SP - 8 R [9]	45	2x280	420	1085	G96108313	22 460
	SP - 8 R	75	4x160	580	1095	G96108463	25 840
FERTILIZER-MICRO	SP - 2 R [9]	75	2x90	190	425	G96102613	9 980
	SP - 4 R [15]	75	2x160	250	725	G96104613	14 825
	SP - 5 R	75	2x160	320	780	G96105613	17 355
	SP - 6 R [15]	45	2x160	250	885	G96106513	19 010
	SP - 6 R [9]	75	2x280	420	915	G96106653	20 410
	SP - 8 R [9]	45	2x280	420	1140	G96108513	24 845
	SP - 8 R	75	4x160	580	1155	G96108663	28 400

[9] Steel fertilizer

[15] Specify in order if the 275 cm frame is desired



DABS Ltd, P.O. box 78037, Dar es Salaam

Phone +255 717593542

www.danagrisol.com